WHAT IS CLAIMED IS:

1. A method for updating configuration information in a TAPI system, comprising:

    storing configuration information in a first configuration table object;

    requesting update static configuration information from a telephony device;

    receiving said update static configuration information; and

    storing said static update configuration information for system use as a second configuration table object.

2. A method in accordance with claim 1, further comprising generating a deleted devices configuration table object and an added devices configuration table object.

3. A method in accordance with claim 2, comprising notifying said TAPI system that each device in said deleted devices configuration table object has been dynamically deleted

4. A method in accordance with claim 2, comprising notifying said TAPI system that each device in said added devices configuration table object has been dynamically deleted.

5. A TAPI system, comprising:

    means for storing configuration information in a first configuration table object;

    means for requesting update static configuration information from a telephony device;

    means for receiving said update static configuration information; and

    means for storing said static update configuration information for system use as a second configuration table object.

1   6. A system in accordance with claim 5, said storing means further comprising
2 means for generating a deleted devices configuration table object and an added
3 devices configuration table object.

1   7. A system in accordance with claim 6, further comprising means for
2 notifying said TAPI system that each device in said deleted devices configuration
3 table object has been dynamically deleted.

1   8.   A system in accordance with claim 6, further comprising means for
2 notifying said TAPI system that each device in said added devices configuration
3 table object has been dynamically deleted.

added